### Introduction

- This document describes the procedure and precautions for upgrading the 2016 NAVIGATION/MULTIMEDIA receiver firmware.
- If an error occurs while you are updating the firmware, the 2016 NAVIGATION/MULTIMEDIA receiver may become unusable. Be sure to read the following procedure and precautions carefully before updating the firmware.

## **Target Model and Firmware Version**

The updater can be used for the firmware versions of the models shown below.

Model group	Target models	Target firmware versions → Updated versions
А	DNX893S, DNX773S, DNX693S, DNX573S	Ver 3.0.0008.0400 or earlier → 3.1.0008.0400
В	DNX716WDABS, DNX5160DABS, DNX5160BTS (Europe), DNX516DABS, DNX3160BT, DNX8160DABS (Europe)	Ver 3.0.0008.0900 or earlier → 3.1.0008.0900
С	DNX8160DABS (Oceania), DNX8160S, DNX8160SM, DNX7160BTS, DNX5160BTS (Latin America)	Ver 3.0.0008.0500 or earlier → 3.1.0008.0500

## Ð

• For how to check your firmware version, refer to "Checking the Firmware Version".

### Work Flow

- Step 1. Download the firmware files, and copy them to USB memory.
- Step 2. Update the firmware. (It takes about 15 minutes.)
- Step 3. Check that the firmware has been updated.

## **Creating the Update Media**

Create the update media on your PC.


- 1. Download the Updates from the Web site.
- 2. Decompress the downloaded file.
- 3. Copy the decompressed file to the top of hierarchy in USB memory.

# 

- USB memory
- File system: FAT 16/32
- Do not copy the updater to a device containing audio files. Blank USB memory is highly recommended.
- Update cannot be performed if it is copied inside a folder.
- If the updater file name is changed, update cannot be performed.

## **Checking the Firmware Version**

1. Press the <MENU> button/ volume knob.




2. Touch [SETUP].



3. 1 Touch [Special]. 2 Touch [2]. 3 Touch [Software Information].



### 4. Check the version.



## **Updating the Program**

- 1. Connect the USB memory. The confirmation message appears.
- 2. Touch [Yes] to update starts. (It takes about 15 minutes.)



**Caution:** The screen may go blank for a few seconds. Do not unplug the USB memory or Power Off the unit during the Update Procedure.

- 3. System Reboot & Software Update Screens
- 4. Once the "Update completed." screen is displayed, remove the USB memory.
- Check that the firmware version is updated, by referring to "Checking the Firmware Version".
  When "3.1.0008.xxxx" is displayed, the firmware version is updated successfully.

#### Precautions

Vx x xxx8

BOOT\_Vx\_...

MAIN\_Vx\_..

UpdateVer...

C S

LE ATK04...

- Update cannot be performed with other media.
- Be sure to park the vehicle in a safe place before updating. Keep the engine running in order to prevent battery from running out.
- Do not turn off the engine or Navigation/Multimedia receiver power while updating. Update cannot be performed correctly and the Navigation/Multimedia receiver may become unusable.