

Project 25 Compliance Assessment Program
Summary Test Report
NX-5700 Mobile Radio, VHF
STR-JKWRD-NX5700-0815

Device Under Test Description	
Manufacturer	JVCKENWOOD Corporation JVCKENWOOD USA Corporation
Manufacturer Contact	Donald E. Wingo, 678-474-4719
Product Name	NX-5700, Mobile Subscriber Unit – VHF
Frequency Band	VHF (136 – 174 MHz)
Installed Options	P25 Conventional P25 Trunking P25 DES (multi-keys) encryption P25 AES (multi-keys) encryption
Installed Vocoder	Enhanced Full Rate

Test Description
P25-CAB-CAI_TEST_REQ - March 2010, Section 2.1.1.1 - Project 25 Phase 1 Common Air Interface Conventional Subscriber Unit Performance
P25-CAB-CAI_TEST_REQ - March 2010, Section 2.1.1.2 - Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability.

Laboratory Information	
P25 CAP Laboratory Number	P25CAP081010 (EFJohnson Technologies)
Date(s) of Test	10 March 2015 – 01 April 2015 25 March 2015 – 13 July 2015
Date of Issue	14 July 2015
P25 CAP Laboratory Number	
P25 CAP Laboratory Number	P25CAP081010 (EFJohnson Technologies)
Date(s) of Test	7 August 2014
Date of Issue	20 August 2014
P25 CAP Laboratory Number	
P25 CAP Laboratory Number	P25CAP081017 (Harris Corporation)
Date(s) of Test	06 November 2014
Date of Issue	10 November 2014
P25 CAP Laboratory Number	
P25 CAP Laboratory Number	P25CAP081011 (Compliance Testing, LLC)
Date(s) of Test	27 May 2015
Date of Issue	02 June 2015

Project 25 Compliance Assessment Program
Summary Test Report
NX-5700 Mobile Radio, VHF
STR-JKWRD-NX5700-0815

Informative References	
Date	Title
March 2010	P25-CAB-CAI_TEST_REQ

Other Devices Tested with: JVCKENWOOD NX-5xxx (Model Class*)

Manufacturer	Product Name, Definition, and Unique ID	Installed Options
EFJohnson	ATLAS, P25 Trunking System	Rel 1..1.0-10, TSNI 1.2.0-14
Harris Corp.	VIDA Premier SR10A MASTR V	Firmware R7G13
Codan Radio	Codan MT-4E – Daniels Trunked Radio	V1.1.0.9

**JVCKENWOOD Model Class is defined as all subscriber units, mobile and portable, that use common software / firmware and hardware design as related to interoperability testing.*

Performance Test Cases and Results

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.1 – Project 25 Phase 1 Common Air Interface Conventional Subscriber Unit Performance		DTR-P25CAP081010-15050401	
Performance – Conventional Receiver Tests NX-5700 (VHF)			
Test Case	Description	Requirement	Results
2.1.4	Reference Sensitivity	≤ -116 dBm	P1
2.1.5	Faded Reference Sensitivity	≤ -108 dBm	P2
2.1.6	Signal Delay Spread Capability	≥ 50 us	P3
2.1.7	Adjacent Channel Rejection	≥ 60 dB	P4
2.1.8	Co-Channel Rejection	≤ 9 dB	P
2.1.9	Spurious Response Rejection	≥ 80 dB	P
2.1.10	Intermodulation Rejection	≥ 75 dB	P
2.1.11	Signal Displacement Bandwidth	≥ 1000 Hz	P
2.1.17	Late Entry Unsquelch Delay		
	No Talk Group or Encryption	≤ 125 ms	P
	Talk Group Only	≤ 370 ms	P
	Encryption Only	≤ 370 ms	P
	Both (On Clear or Encrypted Channel)	≤ 460 ms	P
2.1.18	Receiver Throughput Delay	≤ 125 ms	P

Project 25 Compliance Assessment Program

Summary Test Report

NX-5700 Mobile Radio, VHF

STR-JKWRD-NX5700-0815

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.1 – Project 25 Phase 1 Common Air Interface Conventional Subscriber Unit Performance		DTR-P25CAP081010-15050401	
Performance – Conventional Transmitter Tests NX-5700 (VHF)			
Test Case	Description	Requirement	Results
2.2.8	Unwanted Emissions: Adjacent Channel Power Ratio	≥ 67 dB	P
2.2.12	Transmitter Power Attack Time	≤ 50 ms	P
	Encoder Attack Time	≤ 100 ms	P
2.2.14	Transmitter Throughput Delay	≤ 125 ms	P
2.2.15	Frequency Deviation for C4FM		
	High Level Signal Deviation	$2544 \leq f_{dev} \leq 3111$ Hz	P
	Low Level Signal Deviation	$848 \leq f_{dev} \leq 1037$ Hz	P
2.2.16	Modulation Fidelity	$\leq 5\%$	P
2.2.18	Transient Frequency Behavior		
	Time Interval $t^1 = 5$ ms	$\{\Delta f\} \leq 12.5$ kHz	P
	Time Interval $t^2 = 20$ ms	$\{\Delta f\} \leq 6.25$ kHz	P
	Time Interval $t^3 = 5$ ms	$\{\Delta f\} \leq 12.5$ kHz	P

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance		DTR-P25CAP081010-15071402	
Performance – Trunked Receiver Tests NX-5700 (VHF)			
Test Case	Description	Requirement	Results
2.1.4	Reference Sensitivity	≤ -116 dBm	P1
2.1.5	Faded Reference Sensitivity	≤ -108 dBm	P2
2.1.6	Signal Delay Spread Capability	≥ 50 us	P3
2.1.7	Adjacent Channel Rejection	≥ 60 dB	P4
2.1.8	Co-Channel Rejection	≤ 9 dB	P
2.1.9	Spurious Response Rejection	≥ 80 dB	P
2.1.10	Intermodulation Rejection	≥ 75 dB	P
2.1.11	Signal Displacement Bandwidth	≥ 1000 Hz	P

Project 25 Compliance Assessment Program
Summary Test Report
NX-5700 Mobile Radio, VHF
STR-JKWRD-NX5700-0815

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance		DTR-P25CAP081010-15071402	
Performance – Trunked Transmitter Tests NX-5700 (VHF)			
Test Case	Description	Requirement	Results
2.2.8	Unwanted Emissions: Adjacent Channel Power Ratio	≥ 67 dB	P
2.2.12	Transmitter Power Attack Time	≤ 50 ms	P
		Encoder Attach Time	≤ 100 ms
2.2.14	Transmitter Throughput Delay	≤ 125 ms	P
2.2.15	Frequency Deviation for C4FM		
	High Level Signal Deviation	$2544 \leq f_{dev} \leq 3111$ Hz	P
	Low Level Signal Deviation	$848 \leq f_{dev} \leq 1037$ Hz	P
2.2.16	Modulation Fidelity	$\leq 5\%$	P
2.2.18	Transient Frequency Behavior		
	Time Interval $t^1 = 5$ ms	$\{\Delta f\} \leq 12.5$ kHz	P
	Time Interval $t^2 = 20$ ms	$\{\Delta f\} \leq 6.25$ kHz	P
	Time Interval $t^3 = 5$ ms	$\{\Delta f\} \leq 12.5$ kHz	P

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance		DTR-P25CAP081010-15071402	
Performance – Trunked Transmitter Tests NX-5700 (VHF)			
Test Case	Description	Requirement	Results
2.3.1	Trunking Control Channel Slot Time		
	45 ms Slot		
	Encode Attack Time	$2.0 \text{ ms} \leq t \leq 11.65 \text{ ms}$	P
	RF Power Attack Time	$0.0 \text{ ms} \leq t \leq 11.65 \text{ ms}$	P
	RF Turn Off Time	≤ 1.57 ms	P
2.3.2	Trunking Request Time	≤ 167.5 ms	P
2.3.3	Trunking Voice Access Time	< 500 ms	P5
2.3.5	Transmit Time to Key on Traffic Channel	≤ 150 ms	P

Project 25 Compliance Assessment Program

Summary Test Report

NX-5700 Mobile Radio, VHF

STR-JKWRD-NX5700-0815

Interoperability Test Cases and Results

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability		DTR-P25CAP08101 0-14082001	DTR-P25CAP0810 17-1141104K	DTR-P25CAP0810 11
Kenwood Model Class – NX-5000		EFJ ATLAS	HARRIS VIDA	CODAN
Test Case	Description	Result		
2.2.1	Full Registration			
2.2.1.4.1	Test Case 1 – Valid Registration			
	Home Configuration	P	P	P
	Inter-System Roaming Configuration	N1	N3	N4
	Inter-WACN Roaming Configuration	N1	N3	N4
2.2.1.4.2	Test Case 2 – Denied or Refused Registration			
	Home Configuration	P	P	P
	Inter-System Roaming Configuration	N1	N3	N4
	Inter-WACN Roaming Configuration	N1	N3	N4
2.2.1.4.3	Test Case 3 – Unverified Registration			
	Home Configuration	P	P	N5
	Inter-System Roaming Configuration	N1	N3	N4
	Inter-WACN Roaming Configuration	N1	N3	N4
2.2.2	Group Voice Call			
2.2.2.4.1	Test Case 1 – Group Call Granted			
	Home Configuration	P	P	P
	Inter-System Roaming Configuration	N1	N3	N4
	Inter-WACN Roaming Configuration	N1	N3	N4
2.2.2.4.2	Test Case 2 – Group Call Denied			
	Home Configuration	P	P	P
	Inter-System Roaming Configuration	N1	N3	N4
	Inter-WACN Roaming Configuration	N1	N3	N4
2.2.2.4.3	Test Case 3 – Group Call Request Queued			
	Home Configuration	P	P	P
	Inter-System Roaming Configuration	N1	N3	N4
	Inter-WACN Roaming Configuration	N1	N3	N4

Project 25 Compliance Assessment Program
Summary Test Report
NX-5700 Mobile Radio, VHF
STR-JKWRD-NX5700-0815

2.2.3	Unit-to-Unit Voice Call			
2.2.3.4.1	Test Case 1 – Unit-to-Unit Call with Target Availability Check			
	Home Configuration	P	P	P
	Inter-System Roaming Configuration	N1	N3	N4
2.2.3.4.2	Test Case 2 – Unit-to-Unit Call with Target Availability Check Denied by Target			
	Home Configuration	P	P	P
	Inter-System Roaming Configuration	N1	N3	N4
2.2.3.4.3	Test Case 3 – Unit-to-Unit Call Queued with Target Availability Check – Traffic Channel Assignment After Target Availability Check			
	Home Configuration	P	P	P
	Inter-System Roaming Configuration	N1	N3	N4
2.2.3.4.4	Test Case 4 – Unit-to-Unit Call Queued with Target Availability Check – Traffic Channel Assignment Before Target Availability Check			
	Home Configuration	NA1	NA1	NA1
	Inter-System Roaming Configuration	N1	N3	N4
2.2.3.4.5	Test Case 5 – Unit-to-Unit Call without Target Availability Check			
	Home Configuration	N2	P	N2
	Inter-System Roaming Configuration	N1	N3	N4
2.2.3.4.6	Test Case 6 – Unit-to-Unit Call Queued without Target Availability Check			
	Home Configuration	N2	P	N2
	Inter-System Roaming Configuration	N1	N3	N4
2.2.3.4.7	Test Case 7 – Unit-to-Unit Call Denied			
	Home Configuration	P	P	P
	Inter-System Roaming Configuration	N1	N3	N4

Project 25 Compliance Assessment Program
Summary Test Report
NX-5700 Mobile Radio, VHF
STR-JKWRD-NX5700-0815

2.2.4	Broadcast Voice Call			
2.2.4.4.1	Test Case 1 – Broadcast Voice Call			
	Home Configuration	P	P	P
	Inter-System Roaming Configuration	N1	N3	N4
	Inter-WACN Roaming Configuration	N1	N3	N4
2.2.5	Affiliation			
2.2.5.4.1	Test Case 1 – Radio Permitted to Affiliate with New Group			
	Home Configuration	P	P	P
	Inter-System Roaming Configuration	N1	N3	N4
	Inter-WACN Roaming Configuration	N1	N3	N4
2.2.5.4.2	Test Case 2 – Radio Denied Affiliation to New Group			
	Home Configuration	P	P	P
	Inter-System Roaming Configuration	N1	N3	N4
	Inter-WACN Roaming Configuration	N1	N3	N4
2.2.6	Announcement Group Call			
2.2.6.4.1	Test Case 1 – Collection of Talk Groups Receive Call			
	Home Configuration	P	P	P
	Inter-System Roaming Configuration	N1	N3	N4
	Inter-WACN Roaming Configuration	N1	N3	N4
2.2.7	Emergency Alarm			
2.2.7.4.1	Test Case 1 – Emergency Alarm			
	Home Configuration	P	P	P
	Inter-System Roaming Configuration	N1	N3	N4
	Inter-WACN Roaming Configuration	N1	N3	N4
2.2.8	Emergency Group Call			
2.2.8.4.1	Test Case 1 – Emergency Call			
	Home Configuration	P	P	P
	Inter-System Roaming Configuration	N1	N3	N4
	Inter-WACN Roaming Configuration	N1	N3	N4
2.2.10	Encryption			
2.2.10.4.1	Test Case 1 – Call Privacy for Encrypted Call			
	Home Configuration	P	P	P
	Inter-System Roaming Configuration	N1	N3	N4
	Inter-WACN Roaming Configuration	N1	N3	N4
2.2.11	Intra-Location Registration Area Roaming			
2.2.11.4.1	Test Case 1 – Idle Radio			
	Home Configuration	P	P	N6
	Inter-System Roaming Configuration	N1	N3	N4
	Inter-WACN Roaming Configuration	N1	N3	N4

Project 25 Compliance Assessment Program
Summary Test Report
NX-5700 Mobile Radio, VHF
STR-JKWRD-NX5700-0815

Model Class: NX-5xxx Subscriber	
Product Name, Definitions and Unique ID	Model Number and Installed Options
NX-5700 VHF Mobile	FW K 1.11.01; Trunking, Encryption

Test Case Results Definitions	
No Test Performed	NT
Test Does Not Apply to the Test Object	N/A
Test Object Meets Requirements	P (Pass)
Test Object Does Not Meet Requirements	F (Fail)
Test Object is Not Conclusive	I (Inconclusive)
Comments	
P1: Kenwood subscriber passes Reference Sensitivity specification for C4FM and Simulcast modulations.	
P2: Kenwood subscriber passes Faded Reference Sensitivity specification for C4FM and Simulcast modulations.	
P3: Kenwood subscriber passes Signal Delay Spread Capability specification for C4FM (≥ 50 us) and Simulcast (≥ 80 us) modulations.	
P4: Kenwood subscriber passes Adjacent Channel Rejection specification for C4FM and Simulcast modulations.	
P5: Trunking Voice Access Time will vary dependent on actual system design and implementation.	
N1: EFJohnson infrastructure does not support Inter-System or Inter-WACN roaming.	
N2: Test Cases 2.2.3.4.5 and 2.2.3.4.6 are not supported by EFJohnson and Codan FNE.	
N3: Harris infrastructure does not support Inter-System or Inter-WACN roaming	
N4: Codan infrastructure does not support Inter-System or Inter-WACN roaming	
N5: Codan infrastructure does not support Test Case 3, Section 2.2.1.4.3 Unverified Registration	
N6: Codan infrastructure does not support Intra-Location Registration Area Roaming, Test Case 1, Section 2.2.11.4.1.	
NA1: Test Case 2, Section 2.2.3.4.4 is not applicable to JVCKENWOOD subscribers on EFJ, Harris and Codan infrastructures; see results of test case 2.2.3.4.3	

Project 25 Compliance Assessment Program
Summary Test Report
NX-5700 Mobile Radio, VHF
STR-JKWRD-NX5700-0815

The information contained herein is provided by the manufacturer of the product with permission to make the information publically available. The Department of Homeland Security (DHS) is making this information available as a public service; however, DHS IS PROVIDING THE INFORMATION "AS IS." DHS MAKES NO EXPRESS OR IMPLIED WARRANTIES AND SPECIFICALLY, DHS MAKES NO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THE ACCURACY OR USE OF THIS INFORMATION. Reference to any specific commercial products, processes, or services by trade name, trademark, manufacturer, or otherwise does not constitute or imply an endorsement, or a recommendation, from DHS.

OMB NO: 1640-0015

EXPIRATION DATE: 07/31/2015

Burden Statement

An agency may not conduct or sponsor information collection and a person is not required to respond to this information collection unless it displays a current valid Office of Management and Budget control number and an expiration date. The control number for this collection is 1640-0015 and this form will expire on 07/31/2015. The estimated average time to complete this form is 60 minutes per respondent. If you have any comments regarding the burden estimate you can write to Department of Homeland Security, Science and Technology Directorate, Washington, DC 20528. DHS FORM 10044 – June 2009